

**Amendments to the Claims:**

1. Cancelled
2. Cancelled
3. Cancelled
4. (Amended) The balance shoe according to claim 3 10 wherein one or more guides direct the pivot bar to easily slide into pivot member.
5. Cancelled
6. Cancelled
7. (Amended) The balance shoe according to claim 6 13 wherein the opening has a first ledge and a second ledge and said side support member rides along said first ledge and said pivot member is placed in said opening and pivot member rests on second ledge.
8. Cancelled
9. Cancelled

10. (Amended) An improved balance shoe for retaining a sash in a window jamb channel comprising:

a balance shoe housing having a base section, said base section having at least one channel and at least one side support member slidably movable in said channel from a first position to a second extended position, said channel having a first retaining means and a second retaining means extending from a surface of said channel, said side support member having a retaining arm that moves between said first and second retaining means as said side support member moves from said first position to said second position;

said balance shoe housing having a pivot member, said pivot member having a generally oval-shaped head portion and wherein said oval-shaped head portion engages at least one of said side support members as said oval-shaped portion rotates and forces said side support member of said balance shoe housing to slide in said channel from said first position to said second extended position wherein said side support member is in contact with at least one side wall surface of a window jamb channel when said side support member is in its second extended position and such window is tilted.

11. (Previously Presented) The balance shoe according to claim 10 wherein said side support member has an inner arcuate surface which articulates with said oval head portion as said oval-shaped head portion rotates.

12. (Previously Presented) The balance shoe according to claim 11 wherein said side support member has a serrated surface which engages said window jamb channel when said side support member is in an extended position.

13. (Amended) An improved balance shoe comprising a balance shoe housing having a base section, ~~wherein said~~ base section of said housing ~~has~~ having an opening for receiving and retaining ~~to~~ a pivot member said pivot member being adopted to engage a pivot bar attached to a window sash, said opening having ~~one or more guides~~ a guide that ~~direct~~ directs the pivot ~~mar~~ bar into said pivot member, said guide having a diagonal wall and first and second side diagonal walls on opposite sides thereof to guide said pivot bar into said a pivot member, said pivot member having a generally oval head portion, and wherein said oval head portion of said pivot member forces at least one side support member of said housing outwardly onto contact with at least one sidewall surface of a window jamb channel when said window is tilted and wherein an inner surface of said base section of said housing has a pair of receiving channels cut completely through said housing to permit a retaining arm of the side support member to move freely in a first direction and a second direction in said receiving channel.

14. (New) An improved balance shoe for retaining a sash in a window jamb channel comprising:

a balance shoe housing having a front outer surface and a rear inner surface and a pair of opposed side surfaces connecting said front and rear surfaces, a base section formed by a portion of said front outer and rear inner surface, said front outer surface having at least one channel in the surface thereof, said channel having extending from a surface of said channel a first retaining means and an second retaining means, said channel having at least one side support member slidably movable in said channel from a first position to a second extended position, said side support member having a retaining arm that moves between said first and second retaining means as said side support member moves from said first position

to said second position, said retaining arm being positioned against said first retaining means when a window is in a vertical position and against said second retaining means when said window is in a tilted position;

said balance shoe housing having a pivot member, said pivot member having a generally oval-shaped head portion and wherein said oval-shaped head portion engages at least one of said side support members as said oval-shaped portion rotates and forces said side support member of said balance shoe housing to slide in said channel from said first position to said second extended position wherein said side support member is in contact with at least one side wall surface of a window jamb channel when said side support member is in its second extended position and such window is tilted.

15. (New) The balance shoe according to claim 10 wherein said balance shoe has a first open portion and a second open portion, said second open portion having a rear inner surface an interior top wall and an interior bottom wall and first and second interior side walls, said rear inner surface and said interior walls forming a receiving means for housing a stability member, said interior top wall having a first recess at one end thereof and a second recess at the opposite end thereof.

16. (New) The balance shoe according to claim 10 wherein said housing has an upper diagonal cut and a first and second side diagonal cuts on opposite sides thereof to guide said pivot into said pivot member.

17. (New) The balance shoe according to claim 10 wherein said channel has a first retaining means and a second retaining means on one inside surface of said channel and a

third retaining means and fourth retaining means on a second inside surface of said channel and wherein said side support member has a first and second retaining arm; said first retaining arm being between said first retaining means and said second retaining means and said second retaining arm being between said third retaining means and said fourth retaining means.

18. (New) The balance shoe according to claim 10 wherein said pivot member has front surface and a back surface said back surface having a retaining tab to hold said pivot member in position in said balance shoe housing.

19. (New) The balance shoe housing according to claim 10 wherein said side support member has a recess on each side of said retaining arm.

20. (New) The balance shoe housing according to claim 10 wherein said housing has a recess formed by a rear inner surface and interior sidewalls at opposite ends of said rear inner surface and a separate stability member retained in said recess, said recess having a first region and a second region said first region being deeper than said second region, said stability member having a first bottom edge that fits into said first region and second bottom edge that fits into the second region.

21. (New) The balance shoe housing according to claim 20 wherein said stability member has first slot and a pair of diagonal slots on opposite sides of said first slot.

22. (New) The balance shoe according to claim 21 wherein said stability member has a first and second a retaining member extending therefrom, said retaining members being received by slots in said housing.

23. (New) The balance shoe according to claim 13 wherein said balance shoe has a first open center portion and a second open portion, said second open portion having a rear inner surface an interior top wall and an interior bottom wall and first and second interior side walls, said rear inner surface and said interior walls forming a receiving means for housing a stability member, said interior top wall having a first recess at one end thereof and a second recess at the opposite end thereof.

24. (New) The balance shoe according to claim 13 wherein said channels have a first retaining means and a second retaining means on one inside surface of said channels and a third retaining means and fourth retaining means on a second inside surface of said channels and wherein said side support member has a first and second retaining arm; said first retaining arm being between said first retaining means and said second retaining means and said second retaining arm being between said third retaining means and said fourth retaining means.

25. (New) The balance shoe according to claim 13 wherein said pivot member has front surface and a back surface said back surface having a retaining tab to hold said pivot member in position in said balance shoe housing.

26. (New) The balance shoe housing according to claim 13 wherein said side support member has a recess on each side of said retaining arm.

27. (New) The balance shoe housing according to claim 13 wherein said housing has a recess formed by a rear inner surface and interior sidewalls at opposite ends of said rear inner surface and a separate stability member retained in said recess, said recess having a first region and a second region said first region being deeper than said second region, said stability member having a first bottom edge that fits into said first region and second bottom edge that fits into the second region.

28. (New) The balance shoe housing according to claim 27 wherein said stability member has first slot and a pair of diagonal slots on opposite sides of said first slot.

29. The balance shoe according to claim 28 wherein said stability member has a first and second a retaining member extending therefrom, said retaining members being received by slots in said housing.

30. (New) An improved balance shoe for retaining a sash in a window jamb channel comprising:

a balance shoe housing having a front outer surface and a rear inner surface and a pair of opposed side surfaces connecting said front and rear surfaces, an upper section and a base section said upper section having a recessed portion, said recessed portion having a rear inner surface an interior top wall and an interior bottom wall and first and second interior side walls, said rear inner surface and said interior walls forming a receiving means

for housing a stability member, said recess portion having a first region and a second region said first region being deeper than said second region, said stability member having a first bottom edge that fits into said first region and second bottom edge that fits into the second region, said stability member having a first slot and a pair of diagonal slots on opposite sides of said first slot, said stability member having a first and second a retaining member extending therefrom, said retaining members being received by recesses in said housing;

said base section having at least one channel in a surface thereof, said channel having extending from a surface of said channel a first retaining means and an second retaining means, said channel having at least one side support member slidably movable in said channel from a first position to a second extended position, said side support member having a retaining arm that moves between said first and second retaining means as said side support member moves from said first position to said second position, said retaining arm being positioned against said first retaining means when a window is in a vertical position and against said second retaining means when said window is in a tilted position;

said balance shoe housing having a pivot member, said pivot member having a front surface and a back surface said back surface having a retaining tab to hold said pivot member in position in said balance shoe housing, said pivot member having a generally oval-shaped head portion and wherein said oval-shaped head portion engages at least one of said side support members as said oval-shaped portion rotates and forces said side support member of said balance shoe housing to slide in said channel from said first position to said second extended position wherein said side support member is in contact with at least one side wall surface of a window jamb channel when said side support member is in its second extended position and such window is tilted..